

## Prolumo Bar SLIM – LED light bar, dual position-light

E-approved LED light bar available in 25cm and 52cm with dual-color position lights in "neon-effect". Switch between white and yellow position lights as needed.



Prolumo SLIM are E-approved flat LED light bars with dual built-in LED position lights, illuminating the bottom of the bar in "neon effect". This allows you to switch between white and yellow position lights to match your vehicle perfectly.

Available in 25cm (45W) and 52cm (105W) with a long and sharp high beam. The lights come with both E-approved and NOT E-approved (Off-road/boost) high beams:

25cm E-approved light: 1579 effective lumen

25cm Off-road / boost light: 2703 effective lumen

52cm E-approved light: 3730 effective lumen

52cm Off-road / boost light: 6332 effective raw lumen

The Off-road light is activated by turning on the light for 2 seconds, then turning on and off the light 3 times within 5 seconds. To return to the E-approved light, turn off the light for 5 seconds and repeat. The light remembers the last setting, so no need for reinstallation each time.

The front glass is scratch-resistant and unbreakable, and the light housing is made of powder-coated aluminum for a sleek design and good cooling.

Stainless steel brackets and the included. DT Deutsch connector ensures easy installation.

- Black: Minus / -
- Red: High-beam
- White: White position-light
- Yellow: Yellow position-light

Buy online at:

[www.matronics.eu/24606225](http://www.matronics.eu/24606225)

**Combo, 25cm (45W)**

SKU 24606225

LEDs: 9 x Osram LEDs

Voltage: 10-30V DC

Operating temperature: - 40°C to +60°C

Lumen effective: 2703lm

Lumen, raw: 3780lm

Reference: 20

Kelvin: 5700K

Dimensions: 54,36 x 40 x 246mm

**Combo, 52cm (105W)**

SKU 24606226

LEDs: 21 x Osram LEDs

Voltage: 10-30V DC

Operating temperature: - 40°C to +60°C

Lumen effective: 6332lm

Lumen, raw: 8820lm

Reference: 50

Kelvin: 5700K

Dimensions: 54,36 x 40 x 522mm

Product pictures

