

## Work relay, DIN

Standard relay with one pole, for mounting on DIN rail. Available for 12V, 24V and 230V AC / DC input.



Standard relay with one pole, for mounting on DIN rail, that is used for turning on and off larger loads, or for getting more outputs on a existing installation.

The relay is available with 12V, 24V and 230V AC / DC inputs, and it can switch voltages up to max 250V AC and max 24V DC, while the max current is 16A for 1 poles, 8A for 2 poles

The relay has a red status LED that lights when it is activated..

Buy online at:

[www.matronics.eu/612020](http://www.matronics.eu/612020)

### Specifications

Max voltage	250V AC, 24V DC
Temperature	-20 to 55 degrees
Levetid elektronisk	10.000.000 switches
Lifetime electronics	1.000.000 switches



#### AC / DC 12V, 1 pole

SKU 612020  
Max current: 16A  
Dimensions: 64 x 90 x 18mm



#### AC / DC 12V, 2 pole

SKU 612024  
Max current: 8A



#### AC / DC 24V, 1 pole

SKU 612021  
Max current: 16A  
Dimensions: 64 x 90 x 18mm



#### AC / DC 24V, 2 pole

SKU 612026  
Max current: 8A



#### AC / DC 230V, 1 pole

SKU 612022  
Max current: 16A  
Dimensions: 64 x 90 x 18mm



#### AC / DC 230V, 2 pole

SKU 612026  
Max current: 8A

# Product pictures

