

Prostroke Hideawa - HA4, R65

Bright and compact LED warning strobe, that can be surface mounted on car, MC and truck. Mounted with 2 bolts. UNECE R65 approved.



Hideaway 4 - Bright and compact LED warning strobe lamp, that can be connected to both 12V and 24V, and can be surface mounted on car, MC and truck. The compact house has 4 powerful 3W LEDs, and they create a bright warning together with the special lens, irregardless of placement. The LED lamp is made of aluminum, which makes them very robust against harsh weighing conditions.

The LED lamp is easy mounted with 2 bolts (43mm distance). The included controller is connected to the lamp using the waterproof connectors. The controller is then connected to the power supply.

The controller has 26 programs, where it is possible to switch between 26 different programs that can be synchronized with other connected Prostroke LED lamps. For the dual models, they will split flash in some of the functions.

The LED lamp is ECE R65 approved, and can legally be used throughout Europe and be used on public roads and highways.

You can find further information under downloads, where you can download our datasheet o the product, that has more information regarding the diffent blink patterns / programs.

Dual or single

The single model only has one emitter, dual has two. They have different wire lengths:

Single: 180cm wire

Dual: Emitter 1 has 95cm, emitter 2 has 185cm

The controller itself has 115cm wire on the input, 15cm on the output(s)

Connection

The strobelight connected quite easily as shown below.

- White = Synchronization between other Prostroke units
- Red = Plus warning light (12V-24V)
- Black = Minus
- Yellow = Blink pattern / programs at minus.

Blink pattern

When you pulse the yellow wire on black (minus) for less than 1 second, you switch between the 26 different flash patterns / programs.

In pulse between 1-3 seconds, you switch to the previous flash pattern / program. If the pulse is more than 5 seconds, you turn off the flash pattern / program. If the LED lamp is switched on again, it will continue in the previously selected flash pattern / program.

Reference : 500724, AXIXTECH M53

Buy online at:

www.matronics.eu/731104A

Specifications

Voltage	12V - 24V
Temperature	-30 to 60 grader
Certificates	R65 R10 (EMC)
Flash patterns	26
LEDs	4 x 3W/5W



Yellow, Single

SKU 731104A

Dimensions: 16 x 37 x 55mm



Yellow, Double

SKU 731104DA

Dimensions: 16 x 37 x 55mm

Product pictures

