

T-track guide-rail system - Slider for profiles

Slider that fits in the standard profiles. For guides, fences, and jigs on machines. Built-in adjustment of slide. Two models.

Slider that fits in the standard profiles, where it easily and freely can glide back and forth. The glider can be used for guides, fences, and jigs in machines, where you need linear motion, eg. for a sled on a table saw.

There is M6 thread in the holes and countersunk on the back. The M6 bolts we have on stock with countersunk head are unfortunately a bit too high, so it will require extra countersinking in profile or modifications of the bolts.

The built-in adjustment makes it easy to remove backlash and adjust the force needed to slide.

Difference between the models

The two models differ in the way they can be placed into the track. The "locked" model can only be put into the track from the end of the profile, while the "withdrawable" can be put down from the top, and easily be taken out again. The locked model has some extra rings on the bottom that fits in to the t-track. These can be removed when needed, to make it withdrawable.

Buy online at:

www.matronics.eu/A800200-300

Specifications

Material Aluminium



300mm - Locked

SKU A800200-300

Dimensions: 9,6 x 300 x 19mm



650mm - Locked

SKU A800200-650



300mm - Withdrawable

SKU A800201

Dimensions: 9,6 x 300 x 19mm



450mm - Locked

SKU A800200-450



850mm - Locked

SKU A800200-850