

Strands Siberia DR LED light-bar, E-approved

Strands double-rowed LED light-bar with dual colour position-light in the middle. E-approved for road use.



E-approved LED bars by Strands with dual-colour position-light in the middle making it a stylish and modern look. The LED bars are available in various lengths.

8" version: 4.800 theoretical lumen

12" version: 8.000 theoretical lumen

22" version: 15.000 theoretical lumen

32" version: 24.000 theoretical lumen

42" version: 32.000 theoretical lumen.

The dual-color position-light gives you the possibility to change between white and yellow positions-light as you feel like it so that it fits your vehicle.

The combo-light takes the best of a "spot-" and "flood" light bar. On each side, there are flood lenses, and in the center, spot lenses. This way you have a good combination of the broad light spreading from the sides and the focused light in the center.

The lens glass is produced in polycarbonate and the lamp housing is made of powder-coated aluminum to achieve a sleek design and good cooling for the LEDs.

There are brackets included for mounting and also a pre-mounted 4-pin DT plug, which makes the installation much easier.

- Black: Minus / -
- Red: High-beam
- White: White position-light
- Yellow: Yellow position-light

E-improvements: ECE R112, R7, R10, CE


Ref.: 809179, 809180, 809181, 809182, 809183

matronics

Buy online at www.matronics.eu/24607011


Product overview

DR 8" - 27,5W




SKU 24607010
Voltage: 10-40V DC
Consumption: 27,5W
Lumen theoretical: 4800lm
Lumen effective: 2002lm
Reference: 45
Kelvin: 6000K
Operating temperature: - 30°C to +65°C
Dimensions: 71.6 x 76 x 205mm

DR 12" - 45W




SKU 24607011
LEDs: 20
Voltage: 10-40V DC
Consumption: 45W
Lumen theoretical: 8000lm
Lumen effective: 3294lm
Reference: 45
Kelvin: 6000K
Operating temperature: - 30°C to +65°C
Dimensions: 71.6 x 76 x 307mm

DR 22" - 91W




SKU 24607012
LEDs: 40
Voltage: 10-40V DC
Consumption: 91W
Lumen theoretical: 16000lm
Lumen effective: 6316lm
Reference: 45
Kelvin: 6000K
Operating temperature: - 30°C to +65°C
Dimensions: 71.6 x 76 x 562mm

DR 32" - 143W



SKU 24607013
Voltage: 10-40V DC
Consumption: 143W
Lumen theoretical: 24000lm
Lumen effective: 8792lm
Reference: 50
Kelvin: 6000K
Operating temperature: - 20°C to +45°C
Dimensions: 71.6 x 76 x 817mm

DR 42" - 196W



SKU 24607014
Voltage: 10-40V DC
Consumption: 196W
Lumen theoretical: 32000lm
Lumen effective: 10823lm
Reference: 50
Kelvin: 6000K
Operating temperature: - 20°C to +45°C
Dimensions: 71.6 x 76 x 1072mm

Product pictures



