

Work relay, DIN

Standard relay with one pole, for mounting on DIN rail. Available for 12V, 24V and 230V AC / DC input.



Standard relay with one pole, for mounting on DIN rail, that is used for turning on and off larger loads, or for getting more outputs on a existing installation.

The relay is available with 12V, 24V and 230V AC / DC inputs, and it can switch voltages up to max 250V AC and max 24V DC, while the max current is 16A for 1 poles, 8A for 2 poles

The relay has a red status LED that lights when it is activated..

matronics

Buy online at www.matronics.eu/612020

Specifications

Max voltage	250V AC, 24V DC
Temperature	-20 to 55 degrees
Levetid elektronisk	10.000.000 switches
Lifetime electronics	1.000.000 switches

Product overview

AC / DC 12V, 1 pole



SKU 612020
Max current: 16A
Dimensions: 64 x 90 x 18mm

AC / DC 12V, 2 pole



SKU 612024
Max current: 8A

AC / DC 24V, 1 pole



SKU 612022
Max current: 16A
Dimensions: 64 x 90 x 18mm

AC / DC 24V, 2 pole



SKU 612026
Max current: 8A

AC / DC 230V, 1 pole



SKU 612022
Max current: 16A
Dimensions: 64 x 90 x 18mm

AC / DC 230V, 2 pole



SKU 612026
Max current: 8A

Product pictures

