

DIOSPOT 30 V2 LED Downlight for isolation

Swivel and dimmable LED DIOSPOT Downlight with integrated light source for insulation, available in 3 different colors: white, brushed steel and black.



Swivel and dimmable LED downlight from Diospot with a very low installation height and with an integrated LED bulb at a Ra value / color rendering of 95 out of 100. They are intended to be mounted directly in the insulation ring.

There are several choices for this LED downlight, and you can choose between the colors white, brushed steel and black.

You can also choose between the color temperatures of 2700 Kelvin and 3000 Kelvin, which are all dependent on whether you want a warm, or slightly colder, white light. This LED downlight can be turned / tilted by 20 degrees.

This type of LED downlight is approved for mounting on / in flammable materials, can be relayed with 3G1,5mm², and is dimmable with all common dampers such as e.g. Niko-dimmers. Must be mounted with min. 70 ° C heat-resistant cable and can only be used for indoor use.

matronics

Buy online at www.matronics.eu/606470

Specifications

Cut	75mm
Outer diameter	90mm
Height	32mm
Max. ceiling thickness	30mm

Product overview

White, 2700K



SKU 606470

White, 3000K



SKU 606471

Brushed steel, 2700K



SKU 606472

Brushed steel, 3000K



SKU 606473

Black, 3000K



SKU 606475

Product pictures

