

Prostroke - Spot, R65

Powerful LED warning light, that can be both tilted and rotated. Mounted in a bracket, fastened with a single bolt.



Powerful LED warning light, that can be both tilted and rotated. It is mounted in a bracket, fastened with a single bolt, this makes it perfect for mounting where flat or other warning light cannot be placed. The bracket can also be removed, allowing you to surfacemount it, using the threaded holes on the back.

The spot does NOT work with the other Prostroke lights at the moment, and can therefore NOT be synchronized with these.

The lamp is R65 approved, and can be used on public road.

There are 3 bright 3W high power LEDs in the lamp, and a lens with a wide beam.

Connection

The strobelight connected quite easily as shown below.

- White = Synchronization between other Prostroke units (NOT possible)
- Red = Plus warning light (12V-24V)
- Black = Minus
- Yellow = Blink pattern / programs at minus.

Blink pattern

When you pulse the yellow wire on black (minus) for less than 1 second, you switch between the 26 different flash patterns / programs.

In pulse between 1-3 seconds, you switch to the previous flash pattern / program. If the pulse is more than 5 seconds, you turn off the flash pattern / program. If the LED lamp is switched on again, it will continue in the previously selected flash pattern / program.

matronics

Buy online at www.matronics.eu/731082A

Specifications

Voltage	12V - 24V
Temperature	-30 to 60 grader
Certificates	R65 (warning light) and R10 (EMC)
Flash patterns	26
LEDs	3 x 3W

Product overview

Prostroke - Spot, R65



SKU 731082A
Dimensions: 35 x 52 x 80mm

Product pictures

