

Prolumo Beam XI - LED high-beams, dual position-light

E-approved round LED lightbeams with dual position-light that allows you to switch between white and yellow position-light



LED high-beams with dual position-light, that sits in the top of the lamp without any visible LED's. That gives you the possibility to change between white and yellow positions-light as you feel like it so that it fits your vehicle.

The high-beams are available as 7" (60W) and 9" (120W). These high-beams have 2 light options - one is ECE-approved so that you can use them on public roads and a NOT E-approved (boost) high-beam, that is only for off-road use.

In regards to the light diagram, it shows 1 lux at 430m on the 7" version and 659m on the 9" version with the boost function. You will therefore get more light than the diagram shows and be able to see the reflections in the cones on the side of the road further out.

The boost function is not approved, and therefore not for use on public roads, connected via the plug. To operate in approved mode, the green wire outside the plug should be used.

The lens glass is produced in polycarbonate and the lamp housing is made of powder-coated aluminum to achieve a sleek design and good cooling for the LEDs.

The supplied brackets are manufactured in stainless steel. The lightbars also come with a suitable DT Deutsch-plug, which makes the installation much easier.


- Black: -
- Red: Boost high-beam (Not Approved)
- White: White position-light
- Yellow: Yellow position-light
- Green: E-approved high beam

matronics.nl

Buy online at www.matronics.eu/24606570


Product overview

7" - 60W - 5400lm



SKU 24606570
LEDs: 12 x 5W
Voltage: 9-36V DC
Consumption: 60W
Lumen raw: 7200lm
Lumen, effective: 5400lm
Reference: 30
Kelvin: 6500K
Lifetime: 50000 hours
Weight: 1.2 KG
Operating temperature: -40 to 65 degrees

9" - 120W - 10500lm



SKU 24606571
LEDs: 12 x 10W
Voltage: 9-36V DC
Consumption: 120W
Lumen raw: 13000lm
Lumen effective: 10500lm
Reference: 37,5
Kelvin: 6500K
Lifetime: 50000 hours
Weight: 1.9 KG
Operating temperature: - 40°C to +60°C

Product pictures





